

B17

a'
cont

first and second conduits each having a first end and a second end, said first and second conduits in a first relationship with said first ends of said first and second conduits being substantially adjacent and collinear; and

first means, permitting movement of said inlet opening with respect to said outlet opening to establish a preferred outflow direction, with respect to said inflow direction.

11. A backflow prevention valve, as claimed in claim 10, wherein said backflow prevention valve means includes a first valve disposed in a first portion of said housing and a second valve disposed in a second portion of said housing.

12. A backflow prevention valve, as claimed in claim 11, wherein said first means is located between said first portion of said housing and said second portion of said housing.

13. A backflow prevention valve, as claimed in claim 10, wherein said first means comprises first and second conduits coupled to each other in a substantially leak-free manner.

14. A backflow prevention valve, as claimed in claim 13, wherein said first and second conduits are positioned end-to-end with respect to one another.

15. A backflow prevention valve, as claimed in claim 13, further comprising means for holding said first and second conduits in said end-to-end position in any of a

plurality of rotated configurations with respect to each other.

16. A backflow prevention valve, as claimed in claim 13, further comprising means for sealing the end-to-end region of said first and second conduits against leaking.

17. A backflow prevention valve, as claimed in claim 13, wherein said means for sealing comprises a gasket.

18. A backflow prevention valve comprising:

a housing having an inlet opening and an outlet opening, said inlet opening defining an inflow direction and said outlet opening defining an outflow direction;

backflow prevention valve means disposed in a portion of said housing;

first and second conduits each having a first end and a second end, said first and second conduits in a first relationship with said first ends of said first and second conduits being substantially adjacent and collinear; and

a coupler for holding said first and second conduits in said first relationship in a substantially leak-free manner with said second conduit being in any of a plurality of rotational positions with respect to said first conduit.

19. A backflow prevention valve, as claimed in claim 18, wherein said backflow prevention valve means includes a first valve disposed in a first portion of said housing and a second valve disposed in a second portion of said housing.

*Sub
B1*

20. A backflow prevention valve, as claimed in claim 19, wherein said first means is located between said first portion of said housing and said second portion of said housing.

a' Cont.

21. A backflow prevention valve, as claimed in claim 18 wherein said first and *18* second conduits form a part of said housing.

22. A method for adjusting flow directions in a backflow preventor assembly, comprising:

providing at least one backflow prevention valve;

*Sub
B2*

encompassing said backflow prevention valve in a housing such that said valve automatically closes if flow through said housing drops below a predetermined value, said housing including an inlet opening defining an inlet flow direction, and an outlet opening defining an outlet flow direction;

moving at least a first portion of said housing with respect to a second portion of said housing in a non-screw-threaded relationship, to cause a change in said outlet flow direction with respect to said inlet flow direction to any of a plurality of outlet flow directions in a substantially leak-free manner.

23. A method, as claimed in claim 22, wherein said step of moving comprises:

rotating said first portion with respect to said second portion to place said first and second portions in a desired position;